

H.264 Real Time Embedded DVR



Features:

- * H.264 Real Time
- * 1CH Audio/Alarm
- * Controllo PTZ tramite seriale RS485
- * Multi-linguaggio: Italiano, Inglese, Francese, Tedesco, Spagnolo, Portoghese, Ungherese, Cinese, Turco, Danese, Ceco, Polacco
- * IE monitoring, 3G phone monitoring, E-mail function

Specification:

Modello	DVR7604	DVR7608
Compression Format	H.264	
Video input	BNC(1.0Vp-p/75Ω)×4	BNC(1.0Vp-p/75Ω)×8
Video output	Composite Video: 1.0V pp/75Ω, BNC connector × 1; VGA × 1	
Recording Frame Rate	PAL:100FPS	PAL:200FPS
	NTSC:120FPS	NTSC:240FPS
Audio input/output	1CH/1CH	
Alarm input/output	1CH/1CH	
Alarm	Alarm sensor input; Motion detecting alarm; Video loss alarm; Disk full alarm	
Network mode	10/100M adaptive, support LAN, WAN and ADSL dynamic IP networking	
Monitoring methods	IE monitoring, phone monitoring, E-mail function	
Control	support for the mouse, remote control, PTZ, camera control	
Backup mode	Support USB, Network Backup	
Resolution	Display: (D1) PAL: 704 × 576; Play Back (CIF) :352 × 288	
	Display: (D1) NTSC: 704 × 480; Play Back (CIF):352 × 240	
Hard disk	1pc*2000G	
Security features	Two password management	

Alimentazione	DC 12V/3A-5A
Assorbimento	60W (compreso hard Disk)
Temperatura	Temperatura operativa: +5 °C ~ +50 °C; humidity: <90%
	Temperatura di stoccaggio: -20 °C ~ +70 °C; humidity: <95%
Dimensioni	258×50×238mm(W × H × D)
Peso	1.5Kg



DVR7604 4CH



DVR7608 8CH





Staffa triassiale

Modello	V823HQ
Sensore	1/3" Sony CCD
Sistema di scansione	PAL/NTSC
Sincronismo	Interno
Risoluzione	600TVL
Rapporto S/N	48dB (AGC off)
Illuminazione minima	0 Lux LED on
DNR	Si
Auto gain	+ 18dB max.
BLC	On/Off
Electronic Shutter	On/Off
Specchio	On/Off
Alimentazione	DC 12V
Lente	3.5-8mm varifocal
Temperatura operativa	-10°C-50°C (within 85% RH)
Temp. stoccaggio	-20°C-65°C (within 85% RH)
Staffa triassiale	Si
4 Bit DIP	Si
Portata illuminatore	20m con 17 LED IR
Dimensioni	150mm * 185.5mm (Dia * H)